



# SPY USB

Cold chain monitoring for thermosensitive products during transports



Non-contractual photo

## Presentation

The SPY USB enables cost effective and convenient monitoring of temperature and alarms events during the transport or movement of thermosensitive products used in temperature critical applications such as:

- Sample or product movement within Pharmacies, Hospitals, Clinical labs and Blood Banks
- Logistics: Temperature verification during over-the-road and air shipment of temperature critical products
- Cold chain monitoring during fresh and frozen distribution

The SPY USB is easy to use with two included methods to download data; either via the USB connector integrated into the device or via RFID reader (sold separately). Automatic and secured PDF and Excel reports can be generated after connection to a PC and using the software included.

**The solution is cost effective being available in both single use and multi-use configurations...**

## Benefits

- Direct reading via integrated USB or through packaging using desktop RFID reader (sold separately)
- Automatic and secured PDF (PDF/A1.4) report generated after connection to the PC and using the SPY Soft (included software to be installed only once)
- Monitoring does not stop during the reading and downloading process
- High/low alarm LED indicators on the recorder enable quick on-site decision about product viability
- Activation status ON/OFF LED with manual click button start
- Compact, reliable and light weight



## Technical features

	SINGLE USE	MULTI USE
Temperature range	-30°C to +75°C	
Measurement accuracy	±0,5°C from -20 °C to +40°C and ±1°C out of this range	
Number of uses	2	255
Communication mode	Integrated USB cable - RFID cl. 3- semi passive RFID	
Lifetime	3 years in recording mode	
Starting mode	Manual (immediate or delayed)	
Alarms	Visual indicator - 8 settable thresholds	
Memory	4 000 data points + tracker mode memory	
Dimensions	5.8 x 5.8 x 0.2 cm	
Weight	9.3 gr	
Compliance	CE - NF EN 12830 - WHO PQS - E06TR05 - FCC - FAA	
Protection index	IP65 (exists in IP 68 version) - NEMA5	
Packaging	Pack of 10 pieces	
Delivered with	Gauging certificate in 3 points	
Software	SPY Soft downloaded from www.jri-maxant.com	

# Use

## A efficient software included

- Available in 11 languages (FDA CFR21 Part 11 compliant)
- Installed only once on each recipients PC
- Downloadable via the Internet
- Comprehensive software : configuration, analysis, comments on curves, export to Excel or PDF and automated alert emails
- Lite software « SPY Soft PDF » automatically generating a PDF report for each connection to the PC.

**Multiple Thresholds Configuration**

**Indication of temperature excursions (time and duration)**

**Tracking system**

**Automatic alert by email**

**Export to Excel spreadsheet automatically**

**Automatic PDF report generation**

USB desktop reader allowing fast and efficient data download via RFID communication.

